Dimensions:

42"W x 22"D x 76"H

Part Number:

EXWAZZ0993-LA8

Materials:

Exterior Sides

Side panels shall consist of 7-ply, ¾" thick Red Oak or Maple face and back hardwood veneer core plywood, with PVC edge band

Back

Back panel shall consist of 7-ply, ¾" thick Red Oak or Maple face and back hardwood veneer core plywood, with PVC edge band.

Bottom

Bottom shall consist of 7-ply, 34" thick Red Oak or Maple face and back hardwood veneer core plywood, with PVC edge band.

Top

Top shall consist of 7-ply, ¾" thick Red Oak or Maple face and back hardwood veneer core plywood, with PVC edge band.

Doors

Doors are ¾" Red Oak or Maple face and back on engineered wood core plywood, with PVC edge band. Each door has 3 hinges with a 270 degree range of operation. The pulls on the doors are aluminum pulls.

Drawer Fronts

Drawer fronts are ¾" engineered wood core with 1 mil PVC edge.

Drawers

Drawer Box front panel (1), drawer box back panel (1), drawer box side panels (2) shall consist of rotary cut, maple veneer face and back, 5-ply, ½" thick, veneer core, hardwood plywood with PVC edge banding. Drawer bottom shall consist of poly vinyl coated ½" hardboard fit into a routed groove located in the drawer panels and secured using hot melt glue and 18 gauge pin nails. Drawer bottoms wider than 20" are supported midway underneath with a solid wood spanner support. Drawer box shall be assembled using dovetail or dowel joinery and adhesive. Adhesive shall be a fast setting, ambient cure, water based wood glue.

Drawer Slides

Drawer assembly suspension system shall be ¾ extension, self closing drawer runners (2/drawer).

A coat hook is mounted on the wardrobe door.

A metal coat rod is mounted in the interior of the wardrobe.

Construction:

Glue and Dowel construction throughout.

Finish

Panel surfaces shall be finished on the inside and outside using an ultraviolet cured finish of 100% solid epoxy acrylate, at .3 mil (dry) thick, that emits no volatile organic compounds and contains no formaldehyde.



